



VIDEO DETECTOR INSTALLATION AND EQUIPMENT NOTES

1. THE CONTRACTOR SHALL INSTALL VIDEO DETECTOR ON THE DESIGNATED POLES.
2. DETECTOR AND MOUNTING BRACKETS SHALL BE FURNISHED BY THE CONTRACTOR. ALL OTHER EQUIPMENT AND MATERIALS NECESSARY TO COMPLETE DETECTOR INSTALLATION SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR.
3. THE CONTRACTOR SHALL LABEL AND COIL 10' OF THE STREET WIRING IN THE CONTROLLER CABINET FOR LATER CONNECTION BY CITY FORCES.

NO SCALE

- ① ADJUSTABLE MOUNTING CABLES SHALL BE STAINLESS STEEL
- ② ALUMINUM ALLOY BRACKET WITH HALF CLAMP MOUNTING
- ③ ADJUSTABLE 6061-T6 ALUMINUM MOUNTING BRACKET AS RECOMMENDED BY DETECTOR MANUFACTURER
- ④ 1 1/2" DIAMETER SAPA-B-6061-T6 ALUMINUM PIPE

	DRW: CLK	DATE: 5/15/15	DETECTION - SIGNAL MOUNTING - VIDEO	STANDARD PLATE NO. TRAF-1780-R3
	APP: DRP	DATE: 5/15/15		