



D (IN.)	H (IN.)	W (IN.)	A & B (IN.)	C & BRICK HT. x OR y	LONGITUDINAL STEEL SPACE	INSIDE AREA (SQ. FT.)	FILE NO.*
36	45	30	6, 7	8 x	8 o.c.	7.18	D - 70
39	48 3/4	32 1/2	6 1/2, 7 1/2	8 x	9 o.c.	8.42	D - 69
42	52 1/2	35	6 1/2, 7 1/2	8 x	10 o.c.	9.79	D - 68
45	56 1/4	37 1/2	6 1/2, 7 1/2	8 x	10 o.c.	11.25	D - 67
48	60	40	6 1/2, 7 1/2	8 x	10 1/2 o.c.	12.76	D - 74
51	63 3/4	42 1/2	6 1/2, 7 1/2	8 x	10 o.c.	14.41	D - 66
54	67 1/2	45	6 1/2, 7 1/2	8 y	9 o.c.	16.15	D - 65
57	71 1/4	47 1/2	7, 8	8 y	10 o.c.	18.0	D - 64
48	75	50	7, 8	8 y	10 o.c.	19.94	D - 63
63	78 3/4	52 1/2	7, 8	8 y	10 1/2 o.c.	21.99	D - 62
66	82 1/2	55	8, 9	9 x	11 o.c.	24.13	D - 61
69	86 1/4	57 1/2	7, 9	8 x	11 o.c.	26.37	D - 80
69	86 1/4	57 1/2	9, 11	9 x	12 o.c.	26.37	D - 80A
72	90	60	8, 9	9 x	12 o.c.	28.72	D - 81
75	93	62 1/2	9, 11	9 - 10 x	12 o.c.	31.16	D - 60
75	93	62 1/2	10, 12	9 - 10 x	12 o.c.	31.16	D - 60A

\* = MINNEAPOLIS REFERENCE DRAWINGS

REFERENCE PLATE ONLY

MINNEAPOLIS CUSTOM  
MNDOT SPEC. REF. 2501, 2502, 2503  
MINNEAPOLIS REFERENCE PLATE  
NOT TO SCALE

	DRW: DCD	DATE: 12/02	<b>REINFORCED CONCRETE EGG</b>	<b>STANDARD PLATE NO. SEWR-5008</b>
	APP: HRS	DATE: 1/07		