



- NOTES:
1. ALL FOUNDATION LOCATIONS SHALL BE DETERMINED IN FIELD BY TRAFFIC DIVISION AT TIME OF CONSTRUCTION.
 2. FOUNDATION TOP SHALL HAVE SQUARE EDGES AND BE FINISHED ON ALL SIDES.
 3. CABINET ANCHORS ARE WEDGE ANCHORS, 4 PER CABINET, 1/2" X 4 1/2" STAINLESS STEEL (#304) FULL THREADED.
 - ① 3" FROM HIGHPOINT OF FINISHED SIDEWALK GRADE, 4" FROM HIGHPOINT OF FINISHED BOULEVARD GRADE.
 - ② PROVIDE PROTECTIVE BUSHINGS ON ALL CONDUITS
 - ③ ELECTRICAL CONDUITS AS SPECIFIED
 - ④ KEEP SERVICE FEED TO LEFT OF BARRIER
 - ⑤ TWO GROUND RODS (1/2" X 8') ARE REQUIRED ON ALL SERVICE CABINETS.

NO SCALE

	DRW: EAV	DATE: 11/8/19	FOUNDATION - ST. LIGHT TWO SERVICE CABINETS REFERENCE PLATES: TRAF-3500	STANDARD PLATE NO. TRAF-3088-R1
	APP: DRP	DATE: 11/8/19		