

- 1. ALL FOUNDATION LOCATIONS SHALL BE DETERMINED IN FIELD BY TRAFFIC DIVISION AT TIME OF CONSTRUCTION.
- 2. FOUNDATION TOP SHALL BE FINISHED ON ALL SIDES WITH BROOM FINISH AND EDGED WITH A 1/2" EDGER.
- 3. CABINET ANCHORS ARE WEDGE ANCHORS, 4 PER CABINET, 1/2" X 4 1/2" STAINLESS STEEL (#304) FULL THREADED.
- ↑ 3" FROM HIGHPOINT OF FINISHED SIDEWALK GRADE, 4" FROM HIGHPOINT OF FINISHED BOULEVARD GRADE.
- PROVIDE PROTECTIVE BUSHINGS ON ALL CONDUITS
- **A** ELECTRICAL CONDUITS AS SPECIFIED
- A KEEP SERVICE FEED TO LEFT OF BARRIER
- /5\ TWO GROUND RODS (1/2" X 8') ARE REQUIRED ON ALL SERVICE CABINETS
- ALL DUCTS SHALL BE WITHIN RECTANGULAR OPENING

NO SCALE

DRW: NCR	DATE: 4/5/23
APP: NCR	DATE: 4/5/23

CONTROLLER CABINET TYPE "P" AND ST. LIGHT / DUAL SERVICE CABINET

FOUNDATION - SIGNAL

REFERENCE PLATE: TRAF-3500

STANDARD PLATE NO. TRAF-1071-R7