



**NOTES:**

1. PUSH BUTTON LOCATION SHALL CONFORM TO CURRENT ADA STANDARDS
2. ALL WARNING SIGNS SHALL BE FLOURESCENT YELLOW-GREEN
3. WARNING SIGNS SHALL BE W11-2, W11-15, OR S1-1
4. SEE SPECIAL PROVISIONS FOR RRFB LIGHT BAR REQUIREMENTS

**5** SEE PLANS FOR MOUNTING SIGNS AND LIGHT BARS BACK TO BACK OR SINGLE SIDED

**6**. RRFB PEDESTAL ASSEMBLY MAY BE SUBSTITUTED FOR RRFB OVERHEAD TYPE B ASSEMBLY WHERE THERE IS ONLY ONE APPROACHING LANE OR MEDIAN REFUGE

**7** FOR RRFB OVERHEAD TYPE B ASSEMBLY, SEE STANDARD PLATE TRAF-1243

**8** FOR 30' STREET LIGHT RRFB ASSEMBLY, SEE STANDARD PLATE TRAF-3206. FOR SIGN AND PUSHBUTTON PLACEMENT ON 30' STREET LIGHT, SEE STANDARD PLATE TRAF-1243

**9** FOR RRFB PEDESTAL ASSEMBLY, SEE STANDARD PLATE TRAF-1245



DRW: BKK

DATE: 09/17/18

APP: DRP

DATE: 09/17/18

POLE - SIGNAL

RRFB - INTERSECTION

REFERENCE PLATES: TRAF-1245,  
TRAF-1243, TRAF-7672, TRAF-3206-R4

STANDARD  
PLATE  
NO.  
TRAF-1271-R3