


NOTES:

1. PUSH BUTTON LOCATION SHALL CONFORM TO CURRENT ADA STANDARDS
2. ALL WARNING SIGNS SHALL BE FLOURESCENT YELLOW-GREEN
3. WARNING SIGNS SHALL BE W11-2, W11-15, OR S1-1
4. SEE SPECIAL PROVISIONS FOR RRFB LIGHT BAR REQUIREMENTS

 SEE PLANS FOR MOUNTING SIGNS AND LIGHT BARS BACK TO BACK OR SINGLE SIDED

6. PEDESTAL RRFB MAY BE SUBSTITUTED FOR OVERHEAD RRFB WHERE THERE IS ONLY ONE APPROACHING LANE OR MEDIAN REFUGE

 FOR RRFB OVERHEAD TYPE B ASSEMBLY, SEE STANDARD PLATE TRAF-1243

 FOR 30' STREET LIGHT RRFB ASSEMBLY, SEE STANDARD PLATE TRAF-3206. FOR SIGN AND PUSHBUTTON PLACEMENT ON 30' STREET LIGHT, SEE STANDARD PLATE TRAF-1243



DRW: BKK

DATE: 09/18/18

APP: DRP

DATE: 09/18/18

POLE - SIGNAL

RRFB - MIDBLOCK

REFERENCE PLATES: TRAF-1245,
TRAF-1243, TRAF-7672, TRAF-3206-R4

STANDARD
PLATE
NO.
TRAF-1272-R2